

DRILL RODS AND SUBS – J-Series Drill Rods



DCDMA J-Series Drill Rod – is available from USExploration Equipment Company. The **inertia welded, heat treated tool joints & heavy-wall construction** make the AWJ ideal for SPT work & the NWJ durable enough for rigorous rotary applications. Both thread sizes make-and-break in one & three-quarter turns & **will never cross-thread**. Simply match your desired thread with your required length when ordering...

J-Series Rod features a tapered thread that cannot cross-thread & makes-breaks in 1-1/2-turns

J-Series Drill Rod Assembly	Outside Diameter	Threads Per Inch	Assembly Length	Assembly Weight	Assembly Part Number
AWJ	1-3/4-inch (35mm)	5-TPI	1-Foot (305mm)	3-Pounds (1.4 kg)	27014
AWJ	1-3/4-inch (35mm)	5-TPI	2-Foot (610mm)	6-Pounds (2.7 kg)	27015
AWJ	1-3/4-inch (35mm)	5-TPI	3-Foot (914mm)	11-Pounds (5 kg)	27016
AWJ	1-3/4-inch (35mm)	5-TPI	4-Foot (1.2m)	16-Pounds (7.3 kg)	27136
AWJ	1-3/4-inch (35mm)	5-TPI	5-Foot (1.5m)	20-Pounds (9.1 kg)	27017
AWJ	1-3/4-inch (35mm)	5-TPI	10-Foot (3.1m)	32-Pounds (14.5 kg)	27018
NWJ	2-5/8-inch (67mm)	5-TPI	1-Foot (305mm)	7-Pounds (3.2 kg)	27009
NWJ	2-5/8-inch (67mm)	5-TPI	2-Foot (610mm)	15-Pounds (6.8 kg)	27010
NWJ	2-5/8-inch (67mm)	5-TPI	3-Foot (914mm)	18-Pounds (8.2 kg)	27011
NWJ	2-5/8-inch (67mm)	5-TPI	5-Foot (1.5m)	30-Pounds (13.6 kg)	27012
NWJ	2-5/8-inch (67mm)	5-TPI	10-Foot (3.1m)	60-Pounds (27.2 kg)	27013
J-Series Drill Rod Assembly	Outside Diameter	Threads Per Inch	Assembly Length	Assembly Weight	Assembly Part Number