



4" (102mm) Round Aluminum Locking Well Protector with a Swivel Style Lid, eliminates the need for primer, paint or hinge replacement & NEVER RUSTS!

Locking Well Protectors – Are available from USExploration Equipment Company in a number of different material types and configurations. The Locking Well Protector is installed over a water/monitoring well which finishes above grade. The well protector is typically 5-foot (1.5 m) in length to allow for secure anchoring into the surface surrounding the well. Each assembly includes a **hinged or swivel style** access door. Custom lengths are also available upon request....

Assembly Style	Material Type	Access Door Style	Surface Treatment	Assembly Length	Assembly Part Number
4" x 4" (102mm) Square	Steel	Hinged	Primed	5-Foot (1.5m)	LWPS4
4" x 4" (102mm) Square	Aluminum	Hinged	None Required	5-Foot (1.5m)	LWPA4
4" (102mm) Round	Aluminum	Swivel	None Required	5-Foot (1.5m)	LWPR-A4
6" x 6" (152mm) Square	Steel	Hinged	Primed	5-Foot (1.5m)	LWPS6
6" x 6" (152mm) Square	Aluminum	Hinged	None Required	5-Foot (1.5m)	LWPA6
6" (152mm) Round	Aluminum	Swivel	None Required	5-Foot (1.5m)	LWPR-A6
8" x 8" (203mm) Square	Steel	Hinged	Primed	5-Foot (1.5m)	LWPS8
10" (254mm) Round	Steel	Slip Type	Primed	5-Foot (1.5m)	LWPR-S10