



Hydraulic Double-Rod-Clamp
Specify Drill Pipe, Casing or Drill Rod
sizes when ordering

Hydraulic Double-Rod Clamps - are manufactured by USExploration Equipment Company and can be adapted to most multi-purpose or sonic & roto-sonic drilling rigs. Typically mounted to the base of the mast/ feed frame, these exceptional tooling systems hold rods & casing with the bottom clamp and break the joint with the top (rotating) clamp. This hands-free operation eliminates the need for pipe wrenches, cheater bars or hydraulic breakout wrenches. The operator can simply pull the tool string up through the double-clamp with the head and then crib the down-hole tooling with the bottom clamp, while the top clamp rotates the (exposed) rods or casing until the joint can be spun off and racked for the next hole. Each assembly includes a holding clamp, a breaking clamp & 8-jaw inserts...

Double-Rod Clamp Assembly Breaks Rod with OD	Assembly Part Number
2-1/2-inch (63.5mm) OD thru 7-5/8-inch (193.7mm) OD	7100-500-27164
2-1/2-inch (63.5mm) OD thru 8-5/8-inch (219mm) OD	7100-500-27165

Jaw Inserts (8-Required)	Assembly Part Number
Compact-Sonic Head 2-1/2-inch (63.5mm) OD Thru 7-5/8-inch (193.7mm) OD	500-27162
Compact-Roto-Sonic 2-1/2-inch (63.5mm) OD thru 8-5/8-inch (219mm) OD	500-27163